

A 107 FLEECE
Rev.No: 00
DATE: 01.07.2023
Page No. 1 Of 2

DESCRIPTION

A107 FLEECE is a butyl tape laminated with a non-woven polyester fleece.

KEY FEATURES

Good adhesion to a wide range of substrates.

Remains flexible throughout its service life.

The product is highly conformable.

Easy and accurate to use with little waste and no mess.

The fleece will accept paint, plaster, cement and adhesives.

USES

For sealing floor-to-wall joints and around drains in wet rooms.

For sealing cracks prior to plastering.

For sound-deadening applications.

For applications to prevent air-leakage.

PERFORMANCE

	UNIT	SPECIFICATION	TEST METHOD
Appearance	-	Roll form	TT - 01
Colour	-	Grey	TT - 02
Odour	-	No odour	TT - 03
Specific gravity at 30°C	°C	1.60 -1.80	TT - 05
Dynamic Shear Adhesion	N/cm ²	12	TT - 31
Nonvolatile content at 105 °C for 3hrs	%	Min 99	TT - 09
90° Peel Adhesion	N/cm	Max 0.5	TT - 11
180° Peel Adhesion	N/cm	9	TT - 32
Service Temperature Range	-	No surface crack & adhesion loss	--
Service temperature	°C	-40 to 90 °C	TT - 33

❖ TT- TALON TEST METHOD

A 107 FLEECE**Rev.No: 00****DATE: 01.07.2023****Page No. 1 Of 2****APPLICATION**

- ❖ Application temperature range: 5 to 40 °C
- ❖ **Storage conditions:** Store in cool and dry place at the original packing (Flat position always)
- ❖ **Self-life:** 24months

INSTRUCTION

- **Surface preparation:** All surfaces should be clean, dry, and free from frost, grease, and loose materials. When cleaning contaminated substrates, our recommend that propan-2-ol (IPA) is used and allowed to dry prior to the application of the butyl tape.
- **Application:** Remove the release paper and apply the tape to the substrates to be joined. Take care to avoid rucks in the tape. Roll the tape with a small roller to ensure good adhesion along the whole length of the tape

STD PACKING**Rectangular Section:**

Thickness X Width X Length

1mm x90mmx 10m

1mm x200mmx 10m

TOLERANCES**Rectangular Section:**

Thickness: ± 10%

Width: up to 100mm- ± 2mm
Over 100mm : ± 3mm**GENERAL**

A107 FLEECE butyl tape is part of a range of butyl products for Construction market. For further information, please contact our Customer Care Team or visit our Website.

The information given in this product data sheet is based on laboratory tests and experience which we believe to be correct. Properties quoted are typical and do not therefore constitute a specification. In view of the wide range and variability of substrates, we would advise that our product should be tested by the user to establish suitability for its intended application. E &OE.